



2022 • 2021 • 2020 • 2019 • 2018
EQUIPMENT DEALERS ASSOCIATION
SURVEY | TRACTOR MANUFACTURERS

**PRODUCT
QUALITY**



223

MULTI-PURPOSE
COMPACT TRACTOR

Conquer your to-do list.

We've solved the age-old problem of putting more hours in your day with the all-new SA223.

This next-level model of our popular SA series gets more done than ever before, whether you're working with heavy loads or on difficult terrain. The SA223 is packed with performance upgrades like dual range speeds, standard differential lock, and 3-point hitch position control. Powered by our legendary 3-cylinder, liquid-cooled diesel engine, Yanmar's SA223 always shows up ready to work -- so you can get back to doing what you love.



Dual range speeds, standard differential lock, and true position control on the 3-point lift system for maximum precision and power.

INNOVATIVE DESIGN AND TECHNOLOGY



TRACTORS THAT GET THE JOB DONE.

The SA223 is for people who share our passion for the land and believe in working that land the right way. Not only is it built with a powerful, fuel-efficient engine, its sleek design is engineered for comfort and efficiency all the way down to the easy-access, high-rise hood.



BUILT TOGETHER TO WORK TOGETHER.

Yanmar makes all the major drivetrain components — the engine, transmission, and axles — in-house. And because they're made together to work perfectly together, you get a hardworking machine with more useable horsepower, less power loss, and a smoother, more comfortable ride. We call it Performance Link Technology™. You'll quickly appreciate the SA223 as a tractor designed to work as hard as you do.



COMFORT AND PRODUCTIVITY BUILT RIGHT IN.

A large, comfortable operator's station provides easy access to all controls. The hydrostatic transmission, with convenient side-by-side pedals, allows you to get the job done regardless of the terrain or the implement you're using. And smooth, hydraulic power steering delivers no kickback in the steering wheel for less operator fatigue.

FEATURES

STANDARD DIFFERENTIAL
LOCK

TRUE POSITION CONTROL

DUAL SPEED SYSTEM

4WD SELECTOR

DUAL RANGE HST
TRANSMISSION

LIMITED (CAT1)
3-POINT HITCH



YANMAR 223 Tractor Specifications

ENGINE

| | |
|-------------------------------------|-------------------------------------|
| Maker | YANMAR |
| Model | 3TNM74F |
| Type | 4 Cycle Inline, Water Cooled Diesel |
| Number of Cylinders | 3 |
| Bore and Stroke in (mm) | 2.92x3.03 (74x77) |
| Total Displacement cu In (L) | 60.6 (0.993) |
| Gross Power: EPA Regulation HP (kW) | 21.5 (16.0) |
| Net Power HP (kW) | 19.4 (14.5) |
| Rated Revolution RPM | 3,200 |
| Maximum Torque ft. lbs (Nm) | 39.4 (53.5) |
| Battery | 540 CCA |
| Fuel | Diesel |

CAPACITIES

| | |
|-----------------------------|------------|
| Fuel Tank US gal (L) | 6.1 (23.0) |
| Engine Oil US qt (L) | 3.1 (2.9) |
| Engine Coolant US qt (L) | 3.0 (2.8) |
| Transmission Oil US gal (L) | 4.1 (15.5) |
| Front Axle Oil US gal (L) | 3.17 (3.0) |

DIMENSIONS in. (mm)

| | |
|--|-------------------------------------|
| Overall Length (with 3-Point Hitch) | 102.1 (2,594) |
| Overall Width (with R4 Tires) | 47.3 (1,200) |
| Overall Height (with Roll-Over Protection (ROPS) and R4 Tires) | 82.3 (2,090) |
| Overall Height (with Folded ROPS, R4 Tires, Top Of Steering Wheel) | 66.3 (1,683) |
| Overall Height (with R4 Tires, Top Of Steering Wheel) | 51.1 (1,299) |
| Wheel Base | 57.9 (1,400) |
| Minimum Ground Clearance (with R4 Tires) | 6.4 (163) |
| Tread (with R4) | Front: 35.2 (894), Rear: 35.2 (894) |

WEIGHT lb. (kg)

| | |
|-----------------------|-------------|
| (with ROPS, R4 Tires) | 1,537 (697) |
|-----------------------|-------------|

TRAVELING SYSTEM

| | | |
|-------------------------------|---|--|
| Tires | Ag (R1) Turf (R3) Industrial (R4) | Front, Rear: - Front: 18x8.50-10 4PR, Rear: 26x12.0-12 4PR Front: 18x8.50-10 6PR, Rear: 26x12.0-12 4PR |
| Clutch | | - |
| Steering | | Hydrostatic Power |
| Transmission | | Hydrostatic Transmission, Dual Range Speeds |
| Drive | | Selected 4WD |
| Brake | | Wet Disk |
| Minimum Turning Radius ft (m) | | 7.87 (2.4) |

HYDRAULIC UNIT

| | | |
|--|---|-------------------------------|
| Hydraulic Control System | | Position Control, Open Center |
| Pump Capacity (implement) US gal/min (L/min) | | 4.3 (16.1) |
| Pump Capacity (steering) US gal/min (L/min) | | 3.7 (14.1) |
| 3-Point Hitch | | Limited Category 1 |
| Maximum Lift Force | Lift Point lb (kg) 24 in Behind Lift Point lb (kg) | 660 (300) |
| System Pressure psi (MPa) | | 1,891 (13.00) |

POWER TAKE OFF (PTO)

| | | |
|------------------------------------|--|--|
| Power Take Off (PTO) Power HP (kW) | | 15.6 (11.6) |
| Type | | Hydraulic Clutch |
| Rear | Shaft Size Type Speed/Engine RPM | 35 mm OD, 6 Splines Independent 554/3,200 |
| Mid | Shaft Size Type Speed/Engine RPM | SAE16/32, 15 Splines Independent 2,057/3,200 |

TRAVELING SPEEDS

| | |
|--------------------|---|
| Forward mph (km/h) | Low: 0-4.5 (0-7.3), High 0-9.5 (0-15.2) |
| Reverse mph (km/h) | Low: 0-3.2 (0-5.1), High 0-6.6 (0-10.6) |

YANMAR YL110 CURVED BOOM LOADER SPECIFICATIONS

| | |
|--|--------------|
| Maximum Lift Height to Pivot Pin in (mm) | 71 (1,800) |
| Maximum Lift Height Under Level Bucket in (mm) | 51 (1,295) |
| Reach at Maximum Lift Height in (mm) | 24 (610) |
| Reach with Bucket on Ground in (mm) | 47 (1,205) |
| Digging Depth in (mm) | 3.9 (100) |
| Maximum Drop Angle degree | 40 |
| Maximum Rollback Angle degree | 30 |
| Lift Capacity (Pivot Pin) lb (kg) | 825 (375) |
| Breakout Force (Pivot Pin) lb (kg) | 1,342 (610) |
| Rollback Force (Ground Line) lb (kg) | 1,122 (510) |
| Rated Flow GPM (L/m) | 4.3 (16.1) |
| System Pressure psi (MPa) | 1,891 (13.0) |
| Rising Time to Full Height w/o Load sec | 3.0 |
| Lowering Time w/o Load sec | 1.8 |
| Attachment Rollback Time sec | 2.2 |
| Attachment Dumping Time (REGEN) sec | 1.5 |
| Bucket Width in (mm) | 48 (1,219) |
| Bucket Capacity cu ft (m³) | 5.3 (0.15) |
| Bucket Weight lb (kg) | 130 (59) |
| Loader Weight w/Bucket lb (kg) | 425 (193) |

YANMAR B65 BACKHOE SPECIFICATIONS

| | |
|--|---------------|
| Maximum Digging Depth (2' flat bottom) in (mm) | 78.4 (1,991) |
| Swing Arc | 150 degrees |
| Loading Height (bucket at 60 deg) in (mm) | 60 (1,524) |
| Reach from Center Line of Swing Pivot in (mm) | 102 (2,591) |
| Bucket Rotation | 180 degrees |
| Loading Reach (bucket at 60 deg) in (mm) | 35 (889) |
| Transport Overhang in (mm) | 42.4 (1,077) |
| Undercut in (mm) | 25 (635) |
| Stabilizer Spread, down position in (mm) | 85.6 (2,174) |
| Stabilizer Spread, up position in (mm) | 52.6 (1,336) |
| Bucket Cylinder Digging Force lb (kg) | 2,800 (1,270) |
| Dipperstick Cylinder Digging Force lb (kg) | 1,590 (721) |
| Operating Pressure psi (kg/cm) | 1,885 (132.5) |
| Backhoe Weight lb (kg) | 677 (307) |

YANMAR M60 MID-MOUNT MOWER SPECIFICATIONS

| | |
|------------------------|------------------|
| Mounting Method | Ground Following |
| Cutting Width in (mm) | 60 (1,524) |
| Cutting Height in (mm) | 1-4 (25.4-101.6) |
| Number of Blades | 3 |
| Weight lb (kg) | 283.8 (129) |

AVAILABLE ATTACHMENTS FOR THE YANMAR 223

| | | |
|------------------|-------------|------------------|
| Front End Loader | Front Blade | 3 Pt Attachments |
| Backhoe | Snow Blower | Mid-Mount Mower |

Note: Attachments sold separately. Please see your dealer for details.

ASSEMBLED IN THE USA

All Yanmar tractors are assembled in our state-of-the-art facility in Adairsville, GA, just north of Atlanta. Replacement parts are quickly fulfilled from this location to anywhere in North America. Plus, a ten-year limited powertrain warranty is standard on all new tractor purchases.

DEALERS WHO SHARE OUR COMMITMENT

Yanmar tractors are sold and serviced by a network of dealers who are committed to serving the communities in which they live and work. They share our passion for the land as well as a passion for unsurpassed service. To find the dealer nearest you, please visit YanmarTractor.com.